

Shawver WELL COMPANY INC.

WATER WELL DRILLING AND REPAIRING

P O BOX 266

DIAL 318-237-5341

FREDERICKSBURG, IOWA 50830

April 25, 1978

Erdman Engineering Service
P.O. Box 222
Decorah, Iowa 52101

NEW TOWN WELL---TOWN OF SPILLVILLE, IOWA

LOG OF WELL

0'	to	18'	Soft Broken Limerock
18'	to	177'	Shale
177'	to	200'	Limerock (Galena)
200'	to	395'	Limerock (Galena)
395'	to	472'	Limerock and Shale (Decorah Platteville)
472'	to	480'	Glenwood Shale
480'	to	540'	St. Peter Sand
540'	to	545'	Lime Rock (Prairie Du Chien)

A 15 1/2 inch hole was drilled to 200 feet and a 10 inch pipe was installed and grouted, using a Butler-Larkin Grout Shoe from 200 feet to surface. The 10 inch pipe is 0.365 wall thickness.

The well is then cased from ³⁸⁵~~375~~ feet to ~~485~~ feet with 8 inch Inside-Diameter casing.

An 8 inch hole was then drilled from ~~485~~ feet to 545 feet.

Static water level is 165 feet from ground level.

5-1-78

Dimensions on 8" hole & casing Corrected
after phone call to Geo. Shawver

P.E.