

LOG

oil cube

pump setting

5" - 300' Drop. drop

$8^3 - 8^1$ bowl

4" - 20' TRS! 03 00

S.L. 153

55-60 ppm pumping
- 200

270' P.C. @ 70 p.m.

303
300

1819-5-5

585

farm-house to be
built this spring.

AIR LINE to
Top of bowls
at 300'

Methods for deployment

16" TEMP.
CASING

Спутник

15" HOLE

CEMENT GROUT

140'

DRIFT

SHALE
AND

LIMESTONE

205'

**BROKEN
LIMESTONE
AND
SHALE**

275'

LIMESTONE AND DOLOMITE

10" OPEN
HOLE

CHLORINATED WITH
8 F.F.T.
LINES CHLORINATED

WELL NO. 3

MARCH 12, 1973

CONSTRUCTION

LOG

WELL Completed
MARCH 2, 1973
BY LARUE-WESTERN

same pump
- as in old
well

LARUE pump
9 stages
oil cube
pump setting
5" - 300' Prop. drop
8" - 8' bowl
4" - 20' TRILOPEC
S.L. 153'
55-60 gpm pumping
rate
270' P.C. @ 70 gpm.



Acidified for development

16" TEMP.
CASING

↑ pulled

15" HOLE

CEMENT
GROUT

140'

DRIFT

SHALE
AND

LIMESTONE

205'

BROKEN
LIMESTONE
AND
SHALE

10" 40* BLK.
STEEL
CASING

275'

LIMESTONE
AND
DOLOMITE

10" OPEN
HOLE

575'

1819'-5"

585'
585'

pump-house to be
built this spring

Air Line to
Top of bowl
at 300'