			A CHECK 12 MILL
WASHINGTO	ON PE	RAIRIE CHURCH	-WINNESHIEK, SPRINGFIELD SEC. 12 NW4
R.R.			TATAL R RIM
Decorah,	IA	52101	August 1987
,			1/
			LOG OF WELL
0'	to	50'	Brown clay
50'	to	60'	Limerock 28110.
60'	to	135'	Blue shale
135'	to	160'	Brown shale Mording
160'	to	280'	Brown limerock D 41
280'	to	380'	Brown clay Limerock Blue shale Brown shale Brown limerock Gray limerock
380'	to	435'	Shale
435'	to	460'	Brown limerock
		525'	Brown limerock Sandstone
460'	to	528'	Shale
525'	to	530'	Limerock
528'	to	330	Shale
530'		5701	Limerock
530'	to	570'	Streaks of shale
570'		5001	Limerock
570'	to	590'	JIM OVER
			JIM
590'	t	590½'	Shale
590%	t	(021	Sandstone - made 8 GPM Sandstone - made 8 GPM Alimorock and shale streaks

590' 590½	to to	590½' 603' 615'	Sandstone - made 8 GPM Sandstone, limerock, and shale streaks
603' 615' 618' 627'	to to to	618' 627' 640'	White limerock Sandstone Limerock

The well is cased to 550' with 5" ID X .275 PE casing. A 10" hole was drilled to 550' and cement grout pumped in the annular space.

The static water level is 366'.

The recommended pump setting is 475' at 15 GPM. 8115

Well is probably completed in upper 115' of Prairie du Chien Fru.