

ODW-2

IT 30500

ODW-2 10' E. OF ODW-1

SAMPLE NO.	DEPTH		THICKNESS
	From	To	
1/10/90	0	2	
	2	12	
	12	15	
	15	21	
	21	25	
	25	28	
	28	30	
	30	35	CORE
	35	40	CORE
	40	42	
	42	45	
	45	60	
	60	65	CORE
	65	76	
	76	81	
	81	89	
	89	94	CORE

DESCRIPTION OF BEDS
KIND OF ROCK, COLOR, HARD OR SOFT, WATER, ETC.
TOP SOIL + FILL
LOESS
YELLOW-TAN + YELLOW-BL SILTY CLAY
LOESS
YELLOW-BL SILTY CLAY OR OR. NIS. + BL OR. LAYERS
LOESS
GRAY + YELLOW-GRAY SILTY CLAY
LOESS
BL-GRAY SILTY CLAY
GUMBO
BL-GRAY CLAY TO GRAY CLAY
GUMBO
GRAY + OLIVE GRAY CLAY
(" ")
CLAY + SAND LAYERS
OLIVE + YELLOW-GRAY - YELLOW-BL
YELLOW-OR. TILL SANDY
SANDY GRAVEL
YELLOW-BL TILL
YELLOW-BL. TILL
YELLOW-BL TILL SOME LIGHTER IN COLOR
VERY SANDY YELLOW-BL TILL
GRAY-YELLOW-GRAY + OLIVE TILL
LAYER OF SAND
BL-GRAY TILL LAYER OF YELLOW-BL

ODW-2

PAGE 2

SAMPLE NO.	DEPTH		THICKNESS
	From	To	
	94	120	
1/16/90	(0	120	
	120	130	
	130	135	
	135	171	LARGE BOULDER AT BASE
	171	175	
1/17/90	SET 175' OF 5" PE		
	RUN 175' OF 1 1/8" TIRCO		
	PULLED 1 1/2 TIRCO +		
	BOTTOM OF 5" / CLEAN		
1/18/90	AT WAREHOUSE (CH.)		
1/22/90	175'	301'	
	AIR LIFTED HOLE 1 1/2 H/L		
1/23/90	WL = 200' D.E.		
4/4/90	201.6 BB.		

n.p. = 2.3'

DESCRIPTION OF BEDS

KIND OF ROCK, COLOR, HARD OR SOFT, WATER, ETC.

BL-gray till

REAMING HOLE TO 6 3/4'

BL-gray till SAND LAYERS
occ. BOULDER THIN SAND LAYERS + W/100'BL-gray till SAND + gravel
CEMENTED occ. BOULDER
SAND + gravel some till

TAN + BL L.S.

BLACK STEEL PIPE;

+ RUN 5 SACK CEMENT

PUMPED CEMENT OUT

EL UP + RT. TO AUPPELA

DRILLING 5" HOLE

CLEAN 20 9000