

Northway Well and Pump Co.

W-36832

4895 8th Avenue
Marion, Iowa 52302
Phone 319/377-6339
IA. WATS 1-800-332-3007

Drilled for Muscatine Power and Water at Muscatine

Well is located miles N-E-S-W and miles N-E-S-W from

in the 1/4 1/4 Section 16 Township 76 North Range 2 West of the 5th PM

Drilling started 5-30 1995 Completed 6-2 1995

Well No. 34 Kind of Well Gravel Pack Depth 128' 6" Size hole started 36" in

Finish 36" G. P. M. Static Head Pumping level from surface

Water was first encountered at in Approx. Amt. Temp.

Remarks Well packed with #0 gravel pack

(GIVE DETAILS OF PERFORATED PIPE AND SEALS)

RECORD OF PERMANENT PIPE					TEMPORARY PIPE	
SIZE PIPE	AMOUNT OF PIPE	DEPTH TO BOTTOM OF PIPE	DEPTH TO TOP OF PIPE	MAKE OF PIPE	SIZE PIPE	AMOUNT
24	100'	98' 6"	1' 6" Above GL			
24	30' 7"	128' 6"	98' 6"	SS Screen		
	?			.030 SLOT		

Driller Leon Carpenter From Surface to 128' 6" feet

Driller Dan Glessner From Surface feet to 128' 6" feet

Driller Steve White From Surface feet to 128' 6" feet

AMOUNT IN FEET	KIND OF SOIL OR FORMATION (BE SPECIFIC)	TOTAL DEPTH FEET
2'	Top Soil	2
8'	Course Sand- Small Gravel	10
58'	Fine Sand- Small Gravel 1/8"- 1/4"	68
10'	Gray-Brown Clay	78
6	Sand Gravel 1/4" x 1/2"	84
2	Rocks 6"	86
10	Fine Sand	96
32' 6"	Fine Sand Green- Small Gravel 1/16"-1/4"	128' 6"