

## wediterentedeen lle V

			-					
1.	Contract	Contract City of Markon			Date July 26, 1965			
2.	City and State	City and State iarlan, Ioua			Driller Harold Statz			
3.	Well No. 14 at test hole No. 65-17 Well location (attach map) Approximately 300°							
	northeast of well # 13							
4.	Work completed	July 26, 1	965	No of man hours as charged to job on time sheet				
5.	MATERIAL:	LENGTH	DIA.	GAUGE OR WALL THICKNESS	MATERIAL	TYPE	NO. OF OPENINGS	
6.	Screen	7' 6"	16"	<u>7 ga,</u>	stainless stee	el Lnyne	4	
7.	Inner Casing	31 6"	16"	3/8"	steel	butt weld	***	
8.	Outer Casing	***********	**********	***************************************	***************************************	***************************************	*** ************	
9.	25_tons of g	ravel used in the	well. Size	road grayel	******************************		***************************************	
.0.	Test of well. Did you use test or permanent pump?test							
	Size of orifice							
2.	Pumping test — n	Pumping test — measurements from ground level:						
	TIME G.P.M.		STATIC	DRAWDOWN	PUMPING LEVEL			
			***************************************					
	8:00 A,M10:00 A,M, 165 10:00 A,M 4:00 P,M, 164		14' 6"	•		25 <u>!</u> 6 <u>!</u>		
			14' 6"	11!	25!	25¹6"		
		400440000000000000000000000000000000000	********				***********	
	*********************	**************************************	**********	***************************************	•	***		
•	******************		*****		***************************************	****	••••••	
	************************	######################################	•••••	***************************************	***************************************	•••	•••••	
3.	Recovery in 5 minutes8", in 30 minutes							
4.	Did you seal bottom of well?yea Thickness3/3inches, materialstainlesssteel							
5.	. Well underreamed?noFromfeet tofeet,feet tofeet							
6.	If all screen was not placed at bottom, state how it was spaced.							
	From 25.67 feet to 33 feet; from feet to feet; from feet to feet							
7.	Depth of well from ground level to top of plug33!							
8.	Was cement placed around or between any of the casings?							
9.	. If so, state where, how much and method used							
					***************************************	***************************************		

Page 2

CONTRACT Ciry of Harlan, Iowa Well No.\_\_\_14.... Log of well from ground level: Feet Feet Formation ..... to ..... Black top soil \_\_\_\_\_4..... to .....11..... ..... Gray..clay...... \_\_\_\_11 \_\_\_\_ to \_\_\_\_16 \_\_\_\_ ....Fine and coarse sand, and clay..... .....15...... to ......17...... .....Blue-clsy..... ....Coarse.sendy.gravely.and.fine.send..... ......17:..... to ......31...... \_31\_\_\_\_ to .....33..... -----Gravel -- coarse -- sand -- and -- boulders -------.....Blue-clay..... ......33...... to ......... ..... to ...... ..... to .. ..... to ...... .... to ... \_\_\_\_ to .\_\_\_\_ Depth 33' Gravel Pack 231 10' **Casing** Clay Pack Extension Casing 7'6" 3L' 6" **Drilled Hole**