

1.	Contract	ContractCity of Logan			Date	August 7,	1968	
2.	City and State Logan, Iowa			Driller Harold Statz				
3.				Well location (attach map) 280 south of well # 3				
4.	Work completed8-7-68			No of man hours as charged to job on time sheet				
5.	MATERIAL:	LENGTH	DIA.	GAUGE OR WALL THICKNESS	MATERIAL	ТҮРЕ	NO. OF OPENINGS	
6.	Screen	101	16"	7 ga.	stainless sto	el Layne	3	
7.	nner Casing <u>47</u> 6" 16"		3/8"	steel	steel Butt weld			
8.	Outer Casing	***************************************	********	4*************************************		*************************	****	
9.	15tons of	gravel used in the w	ell. Size.	Coarse ro	ad gravel	************************************	************************	
10.	Test of well. Die	i you use test or pen	manent p	oump? <u>permanent</u>	**********			
11.	Size of Bowl Stages Size of orifice							
12.	Pumping test —	umping test — measurements from ground level:						
	TIME G.P.M.		*****	STATIC	Drawdown	PUMPING	PUMPING LEVEL	
	3.hrs.	3_hrs201		18.*	51 6"	23' 6	231 6"	
	***************************************			ED	•	***		
		LEE	CER	PATT AND THE O		····		
	Recovery in 5 minutes <u>Full</u> , in 30 minutes <u>full</u>							
14.	Did you seal bottom of well?yes							
	. Well underreamed?noFromfeet tofeet,feet tofeet.							
16.	If all screen was not placed at bottom, state how it was spaced.							
	From							
17.	Depth of well from ground level to top of plug							
18.	Was cement placed around or between any of the casings?no.							
19.	If so, state where, how much and method used							
				•			•••••	

CONTRACT City of Logan, Iowa Well No.___5 Log of well from ground level: Feet **Formation** to 0 to 2 to P111 Black top soil _____5¹ ____ to ____16¹ Brown clay Blue clay 16' to 28' .28! to3Q! Blue clay, gravel, and sand 30' to 36' Coarse sand, small gravel, fine sand _____36.¹_____ to ____48.¹_____ Gravel, loosed, coarse sand 48 to 50 Gravel and boulders ____50.1 to ____ Limestone _____ to ____ _____ to to to to to 50' Depth 15 35' **Gravel Pack** Casing Clay Pack Extension 471 6" Casing 10' 42 **Drilled Hale**