

42714

# THORPE WELL COMPANY 2340 SIXTH AVENUE DES MOINES, IOWA

Drilled for Iowa National Guard at Camp Dodge, Iowa  
In parking lot at pistol range  
 Well is located \_\_\_\_\_ miles N-E-S-W and \_\_\_\_\_ miles N-E-S-W from \_\_\_\_\_  
 in the \_\_\_\_\_ 1/4 \_\_\_\_\_ 1/4 Section \_\_\_\_\_ Township \_\_\_\_\_ Range \_\_\_\_\_  
 Drilling started December 3 19 70 Completed December 9, 19 70  
 Well No. 3 Kind of Well Gravel pack Depth 65' Size hole started 30 in  
 Finish 30" G. P. M. 500 Static Head 12' -6 Pumping level from surface 22'  
 Water was first encountered at \_\_\_\_\_ in \_\_\_\_\_ Approx. Amt. \_\_\_\_\_ Temp. 54°  
 Remarks Gravel for pack is Northern gravel, No. 2 size, 16 ton required.

(GIVE DETAILS OF PERFORATED PIPE AND SEALS)

RECORD OF PERMANENT PIPE					TEMPORARY PIPE	
SIZE PIPE	AMOUNT OF PIPE	DEPTH TO BOTTOM OF PIPE	DEPTH TO TOP OF PIPE	MAKE OF PIPE	SIZE PIPE	AMOUNT
10	57'	52'	2' above ground	Steel .365 Wall		
10"	15'	65'	50'	Johnson Stainless Steel Screen 60 Slot		

Driller Bob Wall From Surface to \_\_\_\_\_ feet  
 Driller \_\_\_\_\_ From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Driller \_\_\_\_\_ From \_\_\_\_\_ feet to \_\_\_\_\_ feet

AMOUNT IN FEET

KIND OF SOIL OR FORMATION (BE SPECIFIC)

TOTAL DEPTH FEET

42714

Driller Bob Wall

From Surface to \_\_\_\_\_

Driller \_\_\_\_\_

From \_\_\_\_\_ feet to \_\_\_\_\_

Driller \_\_\_\_\_

From \_\_\_\_\_ feet to \_\_\_\_\_

AMOUNT IN FEET

KIND OF SOIL OR FORMATION (BE SPECIFIC)

TOTAL

4'  
26'  
35'Top Soil  
Blue clay (Silty)  
Sand & Gravel - Boulders at 40'

Received - 09/27/2012