

SOUTH WELL

STATEMENT

Shawver Well Co.

FREDERICKSBURG, IOWA

Phone 4341

In Account With

Town Of Maynard Iowa

Maynard Iowa

JLR	✓
RKS	✓
DJA	✓
KVC	✓
KGG	✓
DISP.	Ken E. E. E.

RECEIVED
IOWA STATE DEPT. OF HEALTH

MAR 29 1976

REGIONAL HEALTH SERVICE NO. 1
MANCHESTER, IOWA

SOUTH WELL

Date	Description	Amount
7 Nov. 1959	235' of 12" Drilling @ 5.00 per ft.	1175.00
	435' of 8" pipe @ 4.00 per ft.	1740.00
	Cementing	15.00
	348' of 8" Drilling @ 4.50 per ft.	1566.00
	67' of 6 1/2" Drilling @ 5.00 per ft.	335.00
	110' of 6 5/8" Oil pipe @ 2.50 per ft.	275.00
	Total	\$5306.00

Log Of Well

0 to 200' Existing 12" Well
 200' to 312' Shale (Maquoketa)
 312' to 372' Limestone (Ft. Atkinson)
 372' to 422' Shale with some limestone
 422' to 435' Limestone (Galena) 235' of 12" hole drilled from original depth of 200' and 435' of 8" pipe installed from ground level to bottom of hole and cemented in place.
 435' to 695' Limestone (Galena) 8" hole
 695' to 703' Shale (Decorah & Glenwood) 6" hole
 703' to 783' Sandstone (St. Peter) 6" hole
 783' to 828' Limestone (Prairie du Chien) 6" hole
 Cased from ground level to 435' with 8" pipe then uncased to (8" hole) 683'. Then from 683' cased with 6" inside diameter or 6 5/8" outside diameter pipe to 793'. From 793' to 850' the hole is uncased.
 Static water level 330' from ground level and did not lower below 420' pumping 100 gallons per minute.

850'
900'
1000'