


10

FARGO, N.D. HUTCHINSON, MN.



DRILLERS LOG

Drilled for _	Orange	City, 1	Iowa								ByFargo				Office
Location of	Test Hole .	Approx.	1000'	Е. с	of	existing	8"	well,	Junction	of	Hickory	& 50	00th		
	•										lo. <u>1</u> –93			."]	L-93
Size of test h	6 3/	/4Date	started _	7-28	3-9	3	D	ate comp	7-29-						

FORMATIONS DRILLED

TYPE OF FORMATION	COLOR OF FORMATION	STARTED AT WHAT DEPTH	ENDED AT WHAT DEPTH	THICKNESS OF FORMATION
. Top soil	black	G.L.	7'	7'
sand and gravel 35+	brown	7 '	25 '	18'
sandy clay (hard)	grey	25'	291	41
sandy clay	grey	29'	631	341
dirty sand w/lenses of clay	grey .	631	80'	17'
very sandy clay	grey	80'	203'	123'
sand w/lenses of clay	grey	203 1	217'	14'
very sandy clay	grey	217'	274'	57'
very sandy shale w/lenses of sandstone	grey	2741	2981.	24'
dirty sand stone (took water) w/lenses of	shale grey	2981	318'	20'
sandstone (took water)	grey	318'	331'	13' .
shale'	grey	331'	333'	2'
sandstone (took water)	grey	333'	341'	8'
shale	grey	341'	347 '	6'
sandstone (took water) drilled good	grey	347'	386'	39'
shale	grey	386'	3881	2'
sandstone	grey	3881	393'	5'
sandstone w/lenses of shale	grey	393'	403'	10'
sandstone (drilled fair) took water	grey	403 '	454 '	51'
sandstone w/lenses of shale	grey	454'	462'	81
shale	grey	462'	468'	6 '
	et.			

Signed	Don	L.	Hejtmanek	_ Drille
Signed		_		DIIII0
