

Shawver Well Company, Inc.

2700 Stanley Avenue
Fredericksburg, IA 50630

77787

(563) 237-5341
(800) 568-4449

Location of Well			Well Details			
	County	Jones	Actual Size	7"	Pump Inst	--
	Township	Washington	Depth	240'	Liner	-- ft
	Section	05	SWL	95'	Screen	--
Latitude	Quarters	SWSWNW	RPS	200' at 30 gpm	Exploratory To	-- ft
Longitude	T&R		Air Lift		Acidize	-- gal
	Elevation		MAX GPM		Water Tests	
					Iron	
					Nitrate	
					Sulfide	--
					Made Water	
Customer Information						
Coohey, Don			Rig			
PO Box 730			Driller			
Cascade, IA 52033			Driller Cert #			
Home Phone:			Assistant			
Work Phone:			Notes			
Cell Phone:			The well is cased to 63' with 7" OD steel x .317 PE casing. A 10' hole was drilled to 62' and Benseal grout was pumped in the annular space.			
Fax:			State Remarks			
Job Information						
Job Use			Confirmation Date			
PWIS #			Start Date			
Permit #			End Date			
Actual Hours			Warranty Date			
			Warranty #			
Formation Log			Bore Hole			
From-To	Color	Formation	From-To	Bit Size		
0 - 18		Sand	0 - 18	12 1/4"		
18 - 120		Limerock	18 - 62	10"		
120 - 234		Gray limerock	62 - 240	6 1/4"		
234 - 235		MADE WATER				
235 - 240		Shale	Casing or Loops			
			From-To	Casing		
			0 - 62	7" OD x .317 Steel		
			Screen Details	Liner Details		
			Screen Size	Liner Size		
			Slot Size	Set From		
			Set From	Perforated From		
			Riser Pipe			
			Tail Pipe			
			Grout Consumed			
			Amount	Unit	Type	
			5	Sk	Benseal	
			2	Sk	Holeplug	
			Product Used			
			Amount	Unit	Type	