

Shawver Well Company, Inc.

2700 Stanley Avenue
Fredericksburg, IA 50630

95926

(563) 237-5341
(800) 568-4449

Location of Well				Well Details			
Public Water Supply		County	Floyd	Actual Size	6 5/8" Steel	Pump Inst	--
1827 Underwood Avenue		Township	Niles	Depth	196'	Liner	-- ft
Charles City, IA 50616		Section	32	SWL	61'	Screen	--
Latitude	43.09375	Quarters	NESENE	RPS	125' @ 18 GPM		
Longitude	-92.63505	T&R		Air Lift	176' @ 25 GPM; 125' @ 18 GPM	Acidize	-- gal
						Made Water	110'-112'; 155'
Customer Information				Driller	Gary Martin		
				Driller Cert #	3845		
Living Hope Mennonite Church				State Remarks			
Fox, Nathan							
11939 Birch Avenue							
Riceville, IA 50466							
Job Information							
Job Use	Chickens						
PWIS #	PWSID#: 3405802	Start Date	11/16/2021				
Permit #		End Date	11/22/2021				
Formation Log				Bore Hole			
From-To	Color	Formation		From-To	Bit Size		
0 - 12		Sand		0 - 60	12 1/4"		
12 - 58	Blue	Clay		60 - 130	9 7/8"		
58 - 75	Brown	Shale & Limestone		130 - 196	6"		
75 - 86	Brown	Limestone		Casing or Loops			
86 - 95	Gray	Limestone		From-To	Casing		
95 - 100	Blue	Shale - Rock		+2 - 130	6 5/8" OD x .28 Steel		
100 - 112	Brown	Limestone		Screen Details	Liner Details		
112 - 114		Limestone - Broken		Screen Size	Liner Size		
114 - 117	Brown	Limestone		Slot Size	Set From		
117 - 120	Gray - Brown	Shale		Set From	Perforated From		
120 - 152	Brown	Limestone		Riser Pipe			
152 - 152		Shale - Rock		Tail Pipe			
152 - 176	Brown	Limestone		Grout Consumed			
176 - 196	Gray	Shale		Amount	Unit	Type	
				90	Sk	Neat Cement	